



HEAVY FIRE VESSEL RED SAILFISH

HEAVY FIRE VESSEL - RED SAILFISH



Principal specifications

| Length overall | 50m |
|--------------------|-------|
| Breadth moulded | 10m |
| Depth to main deck | 5.65m |
| Design draft | 3m |
| Scantling draft | 3.2m |
| Displacement | 600t |
| Gross tonnage | 581 |
| Classification | |

ABS № A1, (E), HSC Coastal Service, Special Government Service, SSR Capable, FFV3, & AMS. & ABCU.

Speed and performance

| Max speed | 20knots at 90% MCR |
|-----------------------|--------------------|
| Cruising speed | 15knots |
| Range | 500NM @ 15knots |
| Dynamic positioning | DPS 0 |
| Operational sea state | SS 3 |
| Survival sea state | SS 5 |

Main machinery

Main engine Propulsion Generator Bow thruster 4 x 1,840kW at 1,800rpm 4 x CPP 3 x 450kWe 2 x 450kW

Tank capacity

Fuel oil Fresh water Lube oil Foam Abt. 175m³ Abt. 10m³ Abt. 2m³ Abt. 16m³

External fire fighting equipment

| Fire pump | 4 x 3,600m³/hr |
|------------------------|-----------------------------|
| Fire monitor | 1 x 3,600m³/hr |
| | 2 x 2,400m³/hr |
| | 1 x 2,400m³/hr foam / water |
| | 2 x 1,200m³/hr |
| | 2 x 600m³/hr foam / water |
| | 2 x 600m³/hr |
| | 2 x 300m³/hr |
| Total monitor capacity | 16,200m³/hr |
| | |

Standby rescue and equipment

2 x 300kg personnel rescue davit 1 x 5.5m RHIB with quick stern launch and recovery system 1 x 5t crane Rescued passengers room - 30pax First-aid room Decontamination area

12

Accommodation

Crew size

CBR protection and detection Ship management system FiFi display mode

ST Engineering Marine Ltd.

Main yard: 7 Benoi Road, Singapore 629882 T: (65) 6861 2244 F: (65) 6861 3028 Tuas yard: 60 Tuas Road, Singapore 638501 T: (65) 6862 2902/3 F: (65) 6862 5382